

Product Group: **Reverse Osmosis**

Part. No: **NRO-MED-350-UG**

Name: **RO Medical permeate capacity 350l/h**

Version: **2.0**

DESCRIPTION:

Computer controlled reverse osmosis system.
Piping and frame is made of high grade stainless steel.

Possibility of membrane extension for more output.

Several conductivity sensors:

- 1x Soft water
- 1x Permeate after membrane
- 1x Permeate loop end

CE Label and Medical Device Class IIb according to Council Directive 93/42/EEC.



- Spiral wound low energy composite polyamide membrane for high recovery;
- Water saving technology with permeate and concentrate re-circulation;
- Piping made of stainless steel (ASI 316)
- Computer controlled system;
- Plain text display;
- Selectable language;
- Manually operated emergency mode in the event of control failure;
- Automatic restart after power failure;
- Operation with HC medical (heat sanitization), serial, parallel, redundant or permeate tank possible;

Technical Data:

Product Output 15°C	350 l/h	Intrastat Code:	8421 21 00
20°C	380 l/h		
Standard Recovery	60-75%	Mains Voltage	230V / 50Hz or 230V / 60 Hz
Salt rejection	<99,3%		115V / 50Hz or 115V / 60 Hz
Room Temperatures	10-35°C	Power rating	2,0 kW
Shipping weight	150 kg	Dimensions (cm):	100x50x165

