



French leader in electrosurgery since 1947

Optima



Universal electrosurgical platform with microprocessors of the latest generation providing energies adapted in real time to the evolution of the tissues (Power Feedback)

Reference: **V10GOPT4**

370 W
Full electrosurgical unit



370 W complete electrosurgical unit, with a wide range of monopolar and bipolar effects

Endosection



Specific waveforms dedicated to endoscopic polypectomy

Argon system



Argon Plasma Coagulation with the optional Argon module for a complete solution for the hepatic and endoscopic surgery

PLASMA™
EDGE



The gold standard of bipolar plasma resection dedicated to bipolar TUR and hysteroresection

THERMOCISION



A unique all-in-one system, which can seal, dissect and cut, dedicated to ENT and other delicate procedures

Vessel sealing



Safe and efficient up to 7 mm diameter, with an acoustic validation signal at the end of the sealing cycle

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A



French leader in electrosurgery since 1947

SPECIAL FEATURES

- Weight : 12Kg / Dimensions : 420mm x 190mm x 430mm (Width x Height x Depth)
- Friendly user interface with an **LCD touch screen** with 170,4 x 127,8 mm size
- Library of more than **80 programs** for all surgical specialties
- Saving more than **1000 personal programs**
- 4 High Frequency outlets: 2 monopolar and 2 bipolar



- Saline cut under saline irrigation with Plasma EDGE technology:
 - TURP/TURB
 - Intra-uterine resection TCRE
- Fulguration / Spray coagulation, without contact
- Optional module for Argon
- Twin simultaneous coagulations
- Recognition and traceability of vessel sealing instruments
- **Reusable cutting and sealing** forceps:
 - * **THERMOCISION™** forceps:
 - Completely **reusable**
 - **Dissection, sealing and cutting** of the vessels in one act
 - * **THERMOCUT™** forceps:
 - Fully **reusable and autoclavable**
 - Safe and efficient sealing up to 7 mm diameter vessels
 - Completely dismountable for a full cleaning
 - Single use blade
 - Cable not attached
 - * **THERMOCLAMP™** forceps:
 - Fully **reusable**
 - **Open surgery** forceps in **16, 22 and 32 cm**

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A



French leader in electrosurgery since 1947

INPUT FEATURES	
<i>Main supply</i>	220 - 240 V ~ (or option 110 - 120 V ~), 50/60 Hz
<i>Safety</i>	Class 1, CF type
<i>Maximum power</i>	1200 VA (600 W)
OUTPUT FEATURES	
<i>Waveform</i>	Pure sinewave and pulsed sinewaves
<i>Fundamental frequency</i>	450 kHz
<i>Modulation frequency</i>	21 kHz

MONOPOLAR CUTS	
AUTOCUT:	
<i>PURE CUT</i>	360 W / 250 Ω
<i>BLEND 1</i>	330 W / 250 Ω, light hemostatic effect
<i>BLEND 2</i>	320 W / 250 Ω, deep hemostatic effect
<i>ENDOCUT 1 / 2</i>	200 W / 250 Ω, for gastrointestinal endoscopy (polypectomies)
FORCED CUTS:	
<i>FORCED PURE CUT</i>	370 W / 450 Ω, forced cut
<i>FORCED BLEND 1</i>	340 W / 450 Ω, forced cut with a light hemostatic effect
<i>FORCED BLEND 2</i>	330 W / 450 Ω, forced cut with a deep hemostatic effect
<i>SPHINCTEROCUT</i>	200 W / 450 Ω, pulsed cut for sphincterotomy

MONOPOLAR CUTS UNDER LIQUID (<i>Glycine solution</i>)	
<i>UROCUT P</i>	350 W / 450 Ω, for transurethral resection of the prostate (TURP)
<i>UROCUT B</i>	350 W / 450 Ω, for transurethral resection of the bladder (TURB)
<i>HYSTEROCUT</i>	320 W / 250 Ω, autocut for hysteroscopic resection (TCRE)

MONOPOLAR COAGULATIONS	
<i>SOFT COAGULATION</i>	170 W / 250 Ω, soft contact coagulation <i>for vascular surgery, pediatric and microsurgery</i>
<i>DESICCATION</i>	210 W / 450 Ω, forced contact coagulation for all surgeries
<i>FULGURATION</i>	100 W / 750 Ω, non-contact coagulation (spray coagulation) for hemostasis of large area
<i>TEAM COAGULATION</i>	100 W / 750 Ω, simultaneous coagulation from 2 monopolar outputs

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
 Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
 RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A



French leader in electrosurgery since 1947

Coagulation with ARGON ¹ (in option), gas flow: 0 to 10 L/min	
<i>CUT UNDER ARGON</i>	Forced cut, 200 W / 450 Ω, under argon jet stream
<i>COAGULATION UNDER ARGON</i>	Forced contact coagulation, 100 W / 450 Ω, under argon jet stream
<i>ARGON PLASMA COAGULATION</i>	Coagulation by ionized gas, 100 W / 750 Ω (open surgery)
<i>PULSED ARGON PLASMA</i>	Coagulation by ionized gas by impulsions, 100 W / 750 Ω (gastrointestinal endoscopy), 3 intervals (ms) t1: 100; t2: 250; t3: 400
Note 1: ARGON modes require an optional module for the control of the Argon gas flow	
BIPOLAR CUT	
<i>PURE CUT</i>	200 W / 150 Ω, cut for the use of bipolar scissors
PLASMA EDGE CUTS UNDER LIQUID ² (NaCl 0,9%)	
<i>THIN LOOP</i>	<i>TURB and TCRE (intra-uterine resection)</i>
<i>THICK LOOP</i>	<i>TURP</i>
<i>VAPORIZATION</i>	<i>TURP and TCRE (intra-uterine resection)</i>
250 W / 300 Ω (display 160)	
BIPOLAR COAGULATIONS	
<i>SOFT COAGULATION</i>	100 W / 25 Ω, for neurosurgery and laparoscopic surgery on vascularized tissues
<i>FORCED COAGULATION²</i>	170 W / 75 Ω (display 100%), for all tissues (vascularized and adipose)
<i>SALINE COAGULATION²</i>	140 W / 75 Ω, for resections under saline solution (Plasma Edge mode)

Note 2: The output power displays in the modes covered by this note are relative displays. (see the power curves in the technical manual of the device)

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
 Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
 RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A



French leader in electrosurgery since 1947

VESSEL SEALING SYSTEM

Maximum power: 150 W / 30 Ω

Sealing of vascular walls up to 7 mm of diameter with reusable thermofusion forceps

The jaws are completely insulated: the thermal spread doesn't exceed 2 mm

Reverse action mode for **THERMOCUT™** handle: the clamping pressure is superior to 700 mmHg

THERMOCLAMP™ forceps for open surgery, with a vessel clamping device

THERMOCUT™ 10 mm diameter forceps for open surgery (20 cm) and laparoscopy (30 cm), with vessel autoclamping system and integrated cut system, straight jaws width 10 mm

THERMOCUT™ 5 mm diameter forceps for open surgery (20 cm) and laparoscopy (30 cm), with vessel autoclamping system and integrated cut system

THERMOCISION™ forceps for dissection, hemostasis and cutting in one act (thyroidectomies)

Automatic output power pre-adjustment following connected forceps

THERMOCONTROL™ program: vessel sealing process monitoring, with sound signal at the end of the cycle and diagnosis of vessel sealing incident

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A



French leader in electrosurgery since 1947

ERGONOMICS	
<i>User interface</i>	Color LCD touch screen
<i>HF power display</i>	Digital display of the maximum power (Watt max.), except for bipolar forced coagulation displayed in % of maximum power
<i>Adjustments</i>	1 W / step on the touch screen
<i>Memorizations</i>	Storage of the setting parameters: selections of the cut and coagulation modes, powers adjustments
<i>Automatic bipolar coagulation</i>	Automatic activation and stop of the bipolar coagulation, by sensing the tissues contact impedance on the forceps tips. 3 available activation delays
<i>Personal programs</i>	Memorization of the surgeons' personal adjustments (<i>possible memorization of several thousand personal adjustments</i>)
<i>MONOPOLAR OUTPUTS</i>	2 outputs for international plugging for hand switches with a 3-pin in-line plug, or for cable with one 4 mm diameter male plug
<i>BIPOLAR OUTPUTS</i>	2 outputs for plugging cables with 2-pin 4 mm diameter male plug (interaxial spacing 28.5 mm)
<i>Twin footswitches</i>	1 socket for controls in: <ul style="list-style-type: none"> • Monopolar and bipolar cuts • Monopolar and bipolar coagulations
<i>Single footswitch</i>	2 sockets for controls in: <ul style="list-style-type: none"> • Bipolar coagulations • Vessel sealing / THERMOCISION™
<i>Hand controls</i>	Hand switches for monopolar cuts and coagulations control and for vessel sealing control on THERMOCUT™ cables

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
 Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
 RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A



French leader in electrosurgery since 1947

SAFETIES	
<i>Neutral electrode safety</i>	Monitoring of the skin contact with a single use adhesive split plate Audible and visual alarm in case of a contact failure or a short circuit, or an electrical discontinuity with inhibition of the HF power Compatible with adult and pediatric plates
<i>Neonatal plates safety</i>	Limitation of monopolar output power up to 50 W, when used with neonatal adhesive double plate
<i>Single plates (option)</i>	Monitoring of the electrical continuity between the unit and the neutral electrode
<i>HF power control</i>	Monitoring of the emitted HF power, with an automatic emission shutdown in case of an excessive HF power (IEC 60601-2-2)
<i>HF leakage currents</i>	$I_{hf} < 100 \text{ mA} / 200 \Omega$ ($< 130 \text{ mA} / 200 \Omega$ in fulguration mode)
<i>Electrical safeties</i>	Class 1, CF type ($I_{lf} < 1 \mu\text{A}$ in Normal Conditions) Defibrillation proof applied parts Short circuit protection $> 10 \text{ s}$
<i>Thermal safeties</i>	Forced ventilation
<i>HF voltage</i>	Regulated (automatic limitation of the voltage)
<i>Limitation of the activation time</i>	Automatic stop after one minute of continuous activation. The normal working is restored after the interruption of the control
<i>Auto checking</i>	When powered on, the unit checks all the connected accessories and internal circuits

LAMIDEY NOURY MEDICAL

Z.A. Les Godets • 3, rue des Petits Ruisseaux • 91370 Verrières-le-Buisson • France
Phone: +33 1 69 20 69 69 • Fax: +33 1 60 13 97 47 • info@lamidey-noury.fr • www.lamidey-noury.com
RCS Evry 445 145 105 • Siret 445 145 105 00018 • TVA FR 49445145105 • Code APE 3250A