

Electrolyte Analyzer

EA-5-25-A EA-5-25-B EA-5-25-D



Features

Economical and practical

A product with a high usage rate and a wide range of users.

Switch on and off at any time, saving reagents, reagent test cost \(\le \) \$0.2

The cost of consumables is low, and the hospital can quickly recover the cost within a few months;



The instrument only has YES and NO keys, concise menu display, simple and clear operation;

Optional automatic sampling, calibration is simple and practical.



Accurate measurement

Adopt advanced ion measuring technology to ensure accurate measurement;

Imported electrode raw materials, long service life.

German CO2 sensor with a service life of up to 10 years;

Adopt automatic potential tracking correction technology to ensure measurement stability;

Measuring range, resolution and accuracy

Items	Measuring Range	Resolution	Measurement accuracy (CV%)
K	0.5-20.0 mmol/L	0.01mmol/L	≤1.0%
Na	15-200 mmol/L	0.1mmol/L	≤1.0%
CI	15-200 mmol/L	0.1mmol/L	≤1.0%
Ca	0.1-6.0 mmol/L	0.01mmol/L	≤1.0%
рН	4-9 pH	0.01pH	≤0.5%

Description

Electrolyte analyzers are indispensable in clinical testing. In clinical practice, it mainly tests and maintains the balance of osmotic pressure in human blood and body fluids; in surgery, burns, diarrhea, acute myocardial infarction and other patients who need a large amount of balanced fluid replacement, the test and detection of ions are very important.

EA Series Electrolyte Analyzers are highly precise and accurate, providing accurate, reliable, fast, and easy-to-use results for any sample. Therefore, ion detection is an essential general equipment for hospitals at all levels.

Advanced technology



Automatic detection and filtering of fine air bubbles, waste liquid overflow alarm function



With power-off protection function, the results can be automatically stored up to 10,000 sets of data;



One analysis can do up to 9 items and 11 parameters (specific version)



The United States imports raw materials and key accessories, and the technical indicators have reached the international advanced level



It can be connected to the LIS system to facilitate hospital management;



Optional automatic sample feeding tray, with automatic cup-seeking detection system



The user can switch the instrument on and off at any time 24 hours as needed to save costs



After sample analysis, it has automatic flushing function to keep the electrode in good standby condition.

Specifications

Model	EA-5-25-A	EA-5-25-B	EA-5-25-D		
Test item	K, Na, Cl	K、Na、Cl、TCO2、AG	K. Na. Cl. iCa. nCa.		
restricti	K NG CI		TCa、pH、TCO2、AG		
Sample Types	Serum, Plasma, V	Serum, Plasma, Whole blood, Cerebrospinal fluid and diluted urine			
Sample consumption	60-300µL(Item 3	60-300µL(Item 3 to item 11)			
Measuring technology	uring technology Ion Selective Electrode				
Analysis time	sis time 25-40 seconds				
Storage	ge Up to 10000 test results				
Printer	Internal thermal	Internal thermal printer			
Ambient Conditions	15-40 °C((60-104	15-40 °C((60-104 F), ≤ 85% humidity			
Communication Interface	RS232				
Optional	Auto sampler: 39 positions (Including 5 emergency and 2 QC)				
Electricity	220V±20V AC, 50Hz-60Hz, ≤120W				
Dimension	ension 380mm*270mm*400mm				
Net weight	weight 7Kg				

01 / VERSION.2022