

PTCA GUIDE WIRES

Features

- 3 mm PT Tip guarantees visibility during X-ray process
- Nitinol Core
- stainless steel with PTFE Coated on the shaft
- Flexibility and maneuverability



| Product No. | Flexibility | Diameter | Tip Load(g) | Length(cm) | Tip Shape |
|-------------|------------------------------|----------|-------------|------------|-----------|
| 42.01.30000 | Super soft-Water snake waist | 0.014" | 0.7 | 190 | Straight |
| 42.01.30001 | Super soft-Water snake waist | 0.014" | 0.7 | 190 | Angled |
| 42.01.30002 | Super soft-Water snake waist | 0.014" | 0.7 | 300 | Straight |
| 42.01.30003 | Super soft-Water snake waist | 0.014" | 0.7 | 300 | Angled |
| 42.01.30004 | Soft | 0.014" | 3 | 190 | Straight |
| 42.01.30005 | Soft | 0.014" | 3 | 190 | Angled |
| 42.01.30006 | Soft | 0.014" | 3 | 300 | Straight |
| 42.01.30007 | Soft | 0.014" | 3 | 300 | Angled |
| 42.01.30008 | Medium-Crocodile Tail | 0.014" | 5 | 190 | Straight |
| 42.01.30009 | Medium-Crocodile Tail | 0.014" | 5 | 190 | Angled |
| 42.01.30010 | Medium-Crocodile Tail | 0.014" | 5 | 300 | Straight |
| 42.01.30011 | Medium-Crocodile Tail | 0.014" | 5 | 300 | Angled |
| 42.01.30012 | Stiff | 0.014" | 9 | 190 | Straight |
| 42.01.30013 | Stiff | 0.014" | 9 | 190 | Angled |
| 42.01.30014 | Stiff | 0.014" | 9 | 300 | Straight |
| 42.01.30015 | Stiff | 0.014" | 9 | 300 | Angled |
| 42.01.30016 | Super stiff-Rhino Horn | 0.014" | 12 | 190 | Straight |
| 42.01.30017 | Super stiff-Rhino Horn | 0.014" | 12 | 190 | Angled |
| 42.01.30018 | Super stiff-Rhino Horn | 0.014" | 12 | 300 | Straight |
| 42.01.30019 | Super stiff-Rhino Horn | 0.014" | 12 | 300 | Angled |