

PowerEdge R760xs 2U Intel Xeon Silver 4510 2.4G, 12C/24T, 16GT/s, 30M Cache, Turbo, HT (150W) DDR5-4400, 1x 32GB RDIMM, 5600MT/s, Dual Rank, No HDD, PERC H755 Adapter, Low Profile, iDRAC9, Enterprise 16G, Broadcom 5720 Dual Port 1Gb On-Board LOM, MLK, Broadcom 5719 Quad Port 1GbE BASE-T Adapter, PCIe Low Profile, 3.5" Chassis with up to 12 Hard Drives (SAS/SATA) PERC11, Standard Bezel, Riser Config 0, No Riser, 1x16 + 1x8 (1 CPU), without OCP, No OCP 3.0 mezzanine NIC card, Blank Filler Only, Dual, (1+1)RDNT, Hot-Plug PSU, 700W MM HLAC (200-240V ONLY, not for 100-120V outlet) Titanium, 2x C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord, Trusted Platform Module 2.0 V6, High Performance Fan x5, High Performance Heatsink, ReadyRails Sliding Rails Without Cable Management Arm, 3Yr ProSupport and Next Business Day Onsite

Intel Xeon Silver 4510 2.4G 12C/24T 16GT/s 30M Cache Turbo HT (150W) DDR5-4400 Customer Install

Standard Heatsink, PowerEdge R760xs, Cus Kit

3x Memorie 32GB DELL RDIMM 2Rx8 DDR5 5600MT/s (Not Compatible with 4800 MT/s DIMMs)

2x 960GB SSD SATA Dell Read Intensive 6Gbps 512e 2.5in with 3.5in HYB CARR, S4520, CUS Kit (compatibil G14&G15)

4x HDD 8TB NL-SAS Dell 12Gbps 7.2K 512e 3.5in Hot-Plug, Customer Kit (Compatibil Gen 14th si 15th)

Windows Server 2025 Standard, ROK,16CORE (for Distributor sale only)

4x Windows Server 2025 Standard Edition Add License2CORE NO MEDIA/KEY Cus Kit