

AMINOL M-14B2 Mineral Engine Oil

Description and Application

- **AMINOL M-14B2** Motor oil is designed for lubrication of two- and four-cycle diesel, ship and stationary diesel engines with their operation on distillate diesel fuels with a sulfur content of up to 0.5% (mass fraction), as well as quarry dump trucks. It is made on the basis of mineral base oils, contains a balanced composition of additives, providing the required level of performance.

Benefits

- It has good detergent properties, low volatility and insignificant loss of carbon monoxide.
- Stability at high operating temperatures protects engine parts from deposits.

Specification

SAE 40	
API	CB

AMINOL M-14B2

Mineral Engine Oil

Typical physical and chemical characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	ASTM D 4052	0.892
Kinematic Viscosity at 100°C, mm ² /s	ASTM D 445	13.8
Viscosity Index	ASTM D 2270	87
Flash point COC, °C	ASTM D 92	228
Pour point, °C	ASTM D 97	-12
TBN (HClO ₄), mg KOH/g	ASTM D 2896	5.0
Sulfated Ash, %	ASTM D874	1.0

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by reasonable production tolerances. The right to make modifications is reserved.

Health, safety and product handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.aminol.az

Packing options:

